



# NEPOLIN EXTERIOR EMULSION

Nepolin exterior emulsion is an acrylic emulsion based paint suitable for exterior in dry and less humid weather conditions.

**Features**

- Good Hiding
- Anti algal

**Technical Data**

Physical Properties	Specification
<b>Bases</b>	NXB-1, NXB-10, NXB-13, NXB-15, NXB-20
<b>Color Range</b>	Refer to our Color Bazaar Ambience Plus Fandek
<b>Finish</b>	Flat, Smooth
<b>*Theoretical Coverage</b>	10-12 sq. meter, per ltr, 1 coats (actual coverage depends surface condition)
<b>Dry Time</b>	30 min (Recoat Time : 4-6 hrs)
<b>Clean Up Solvent</b>	Clean Portable Water
<b>Stability of Diluted Paints</b>	24hrs
<b>Recommended Primer</b>	Pashupati Paints Ex-Coat Exterior Primer( Through DTS)
<b>Thinning Ratio</b>	<b>Brush or Roller:</b> 1ltr part and 400 ml water by Volume <b>Conventional:</b> 2-3 part paint and 400 ml water (10%) by volume

**Application procedure and recommendation for best performance**

Surface Type	Step 1	Step 2	Step 3	Step 4
New Surface	Self Primer(1coat): Nepolin Acrylic Exterior Emulsion Paint	Putty: Ready Made - Wall Guard Cement Base Putty	Self Primer(1coat): Nepolin Acrylic Exterior Emulsion Paint	Finish (2coats): Nepolin Exterior Emulsion Paint
Pre-Painted Prepared Surface	Primer(2coat) Nepolin Exterior Primer	Finish (2coats): Nepolin Acrylic Exterior Emulsion Paint		
Emulsion Painted Prepared Surface	Primer (2coats) No Primer	Finish (2coats): Nepolin Acrylic Exterior Emulsion Paint		

**Note:** For dark shades, additional cost may apply for complete hiding.

## Precaution

---

- Keep it out of reach of children.
- Stir well and strain before use. Follow safety, health and environmental information.
- Do not apply when ambient temperature is less than 10°C otherwise drying of finish paint will be delayed.
- Do not use any other company's universal strainers or colorants.
- Do not over thin or apply on powdery, chalky or damp surface.
- To avoid premature paint failure, apply finish coats within 24 hours of primer coat.
- Avoid use of plaster of Paris and its mixture to fill dents, gaps and cracks.
- To avoid inconsistency or variation in Color Bazaar shades make sure that base colorants are mixed properly as required.
- It is advisable to apply the paint during dry weather. Application must be avoided in wet and rainy season.

## Safety Health and Environmental Instruction

---

- Container must be kept tightly closed, in a secure, upright position.
- Keep away from source of food, drink, animal feed and children.
- Do not breathe vapour or spray, keep doors and windows open during application.
- Put on air-supply breathing mask while sanding and painting especially in confined space.
- Put on eye glasses for eye protection in case of eye contact, rinse immediately with plenty of water and seek medical advice.
- After application use soap and water or paints – cleaner for hand external body parts.
- Do not dispose paint by throwing in any drain/water channel. Dispose it in a land – fill area only.



### Pashupati Paints Pvt. Ltd.

Registered office at Biratnagar, Nepal

Registered Branch office at Kathmandu, Pokhara, Butwal, Nepal

**Pashupati Paints**

खुशीका रंगहरु

## Note

---

The information is given in good faith but without any warranty. We reserve the right to change the data without prior notice due to continuous R&D.

\* Covering capacity is the result obtained on well prepared smooth surface, hence it may change from surface to surface